Datasheet

DNAKE TWK04



Instruction

Embrace security with a simple touch. DNAKE 2-wire Intercom kit is a complete solution that includes a door station, an indoor monitor, and accessories to mount. The new 2-wire intercom kit is immediately ready for use. Improve your safety at home while increasing convenience with DNAKE 2-wire Intercom Kit!

Key Features

- 2-Wire Connection
- 7-inch touchscreen
- Wi-Fi connection
- IP65 / IK07 Rating
- Multiple Access Options
- Mobile App Remote Control



Datasheet

Key Features

- Easy configuration
- 7-inch TFT capacitive touch screen
- Wi-Fi connection
- TF Card Slot
- Support monitoring 8 IP cameras

Physical

- System: Linux
- Front Panel: Plastic
- Power Supply: DC 24V
- Standby Power: 5 W
- Rated Power: 9.5 W
- Wi-Fi: Support 802.11b/g/n 2.4G
- TF Card Slot: 1 X 32G maximum
- Relay Output: 1
- Doorbell Input: 1
- Installation: Surface Mounting
- Dimension: 195 x 130 x 17.6 mm
- Working Temperature: -10°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-

condensing)

DNAKE E217W-2



Display

- Display: 7-inch TFT LCD
- Screen: Capacitive touch screen
- Resolution: 1024 x 600

Audio

- Audio Codec: G.711
- Echo Cancellation
- Microphone: Built-in microphone
- Speaker: Built-in speaker

Video

Video Codec: H.264

Datasheet

Key Features

- 110° wide-angle 2MP HD camera
- Support IC (13.56MHz) card, PIN Code
- 2 Lock Controls (1 relay out, 1 electronic lock)
- Tamper Alarm
- IP65 / IK07 Rating

DNAKE S213K-2



Physical

System: Linux

RAM: 64 MB

ROM: 128 MB

• Front Panel: Aluminum

Power Supply: Powered by Indoor Monitor

Standby Power: 3.5 W

Rated Power: 12 W

Camera: 2MP, CMOS

Door Entry: IC card (13.56MHz), PIN code

Lock Control: 2 (1 relay out, 1 electronic lock)

IP / IK Rating: IP65 / IK07

Installation: Surface Mounting

Dimension: 188 x 88 x 34 mm

Working Temperature: -40°C to +55°C

Storage Temperature: -40°C to +70°C

Working Humidity: 10% to 90% (non-condensing)

Audio

Audio Codec: G.711

Echo Cancellation

• Microphone: Built-in microphone

Speaker: Built-in speaker

Video

Video Codec: H.264

• Video Resolution: 1280 x 720

Viewing angle: 110°(H) / 60°(V) / 125°(D)

Max. Image Transfer Rate: 720p – 25fps

• Light Compensation: LED white light