

DH-IPC-EBW81242

12MP Panoramic Network IR Fisheye Camera



- 12MP, 1/1.7"CMOS image sensor
- Max output 12MP (4000×3000)@30fps
- 3D DNR,AWB,HLC, BLC,ROI, SVC, SMART H.264/H.265
- People counting in multiple areas, queuing management in multiple areas, heat map (number of people /time), and track map
- 2/2 Alarm in/out, 1/1 audio in/out
- 12V DC/POE power support
- IP67, IK10 protection



System Overview

With advanced chip and deep learning algorithm, AI Fisheye network camera supports many intelligent functions, including people counting in multiple areas, multiple queues management, heat map of number of people and average strand time.

Functions

People Counting

The camera detects and tracks target by using advanced image processing technology and deep learning algorithm. You can draw 4 ploygon areas, and count people in each area; When the number of the people in the area is greater than or equal to/lower than or equal to the defined threshold, the alarm will be triggered.

Queue Management

The camera detects and tracks target by using advanced image processing technology and deep learning algorithm. You can draw 4 ploygon areas, and count people in each area; When the number of the people in the area or the strand time is greater than or equal to/lower than or equal to the defined threshold, the alarm will be triggered.

Heat Map

It supports heat map of number of people and average strand time. You can observe customer's regions of interest from two aspects: number of people and time.

Technical Specification				
Camera				
Image Sensor	1/1.7” CMOS			
Effective Pixels	4000 (H) × 3000 (V)			
ROM	4 GB			
RAM	4 GB			
IR LEDs	3 (IR LEDs)			
Electronic Shutter Speed	1/3 s-1/100000 s (Auto/Manual)			
Min. Illumination	0.001 Lux/F2.0 (Clolor, 1/3 s, 30 IRE) 0.01 Lux/F2.0 (Clolor, 1/30 s, 30 IRE) 0 Lux/F2.0 (IR on)			
IR Distance	10 m (32.8 ft)			
Scan	Progressive			
Noise Reduction	3D DNR			
WDR	DWDR			
S/N Ratio	49.7dB			
Gain control	Manual			
White Balance	Auto/Natural/street lamp/outdoor/manual/regional Custom			
Lens				
Focal Length	1.85 mm			
Mount Type	M12			
Max. Aperture	F2.0			
Aperture Type	Fixed aperture			
Lens Type	Fixed focal			
Field of View	Horizontal: 185°; Vertical: 180°			
DORI Distance	Detect	Observe	Recognize	Identify
	40.0 m (131.3 ft)	16.0 m (52.6 ft)	8.0 m (26.3 ft)	4.0 m (13.1 ft)
Audio				
Audio Input	1 channel (RCA port),1 build in MIC			
Audio Output	1 channel (RCA port)			
Audio Encoding	G.711A, G.711Mu, G726, AAC			
Video				
Video Encoding	H.265, H.264, H.264H, H.264B, MJPEG			
Video Bit Rate	H264: 88Kbps-16384Kbps ;H265: 52Kbps-16384Kbps			
Video Frame Rate	50Hz Main Stream (4000 × 3000@25fps), sub Stream (704 × 576@25fps), third Stream (704 × 576@25fps) 60Hz Stream (4000 × 3000@30fps), sub Stream (704 × 480@30fps), third Stream (704 × 480@30fps) Fisheye: 1O (4000 x 3000) 1P (4096 x 1024) 2P (2432 x 2432) 1R (1216 x 1216) 2R (2432 x2432) 4R (2432 x 2432) 1O + 3R (2432 x 2432)			

Resolution	4000 × 3000, 2880 × 2880, 2880 × 2160, 2048 × 1536 (3M), 1280 × 960 (1.3M), (704 × 576/704 × 480) D1, (352 × 288/352 × 240) CIF
Bit Rate Control	CBR/VBR
Region of Interest	Yes (4 areas)
Smart IR	Yes (Adjust by user)
Language	English, Italian, Spanish, Russian, French, German, Portuguese, Polish, Korean, Persian, Czech, Dutch, Arabic, European Spanish
Alarm	
Alarm Input	2 channels (Wet contact, and it supports max potential 3V-5V)
Alarm Output	2 channels (Dry contact, and it supports max potential 30V)
Function	
SD Card	Yes
Storage	FTP, Micro SD card (256 G)
Max User	20 (Total bandwidth: 240 M)
Browser	IE: IE11, IE10, IE9 Google of high version: 48.0.2564.116 Firefox of high version: 48.0.2 Non-plug edge: 42.17134.1.0
Privacy Masking	4 areas
Smart event	
IVS Analyze	Intrusion, tripwire
Heat Map	Yes
Professional, intelligent	
People Counting	People counting in 4 areas, number of people threshold alarm, 4 queue management, stranding alarm, number of people alarm, number of people heat map, average stranding heat map, track map and export (Report max range is 1 week.)
Network and port	
Network Protocol	HTTP, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, SNMP, QoS, UPnP, NTP
Interoperability	ONVIF (Profile S/Profile G), GB/T28181, CGI
General	
Power Supply	12V DC /POE
Power Consumption	Basic power consumption: 6.2W (12V DC), 9.2W (POE) Max power consumption: (ICR switch, and IR full intensity): 9.2W (12V DC), 12.9W (POE)
Operating Temperature	-30°C to +45°C (-22°F to +113°F)
Operating Humidity	≤95%
StrorageTemperature	-30°C to +70°C (-22°F to +158°F)
Strorage Humidity	≤95%
Protection Grade	IP67, IK10
Enclosure	Metal + Plastic

Dimensions	59.8 mm × Ø149.8 mm (2.35" × Ø5.9")
Net Weight	0.77 kg(1.70 lb)
Gross Weight	1.16 kg(2.56 lb)
Certification	CE-LVD:EN60950-1 EN 55032: 2015, Class B EN 61000-3-2: 2014 EN 61000-3-3: 2013 EN 55024: 2010+A1: 2015 EN 55035: 2017 EN 50130-4: 2011+A1: 2014 CE-EMC:Electromagnetic Compatibility Directive 2014/30/EU FCC:47 CFR FCC Part15, Subpart B, Class B UL/CUL:UL60950-1 CAN/CSA C22.2 No.60950-1-07

Ordering Information

Type	Part Number	Description
Fisheye	DH-IPC-BW81242P	12MP AI Fisheye Dome Network Camera
	DH-IPC-BW81242N	
	IPC-EBW81242P	
	IPC-EBW81242N	
Accessories (optional)	DH-PFA100	Adapting plate
	DH-PFA132-E	Junction Box
	DH-PFB302S	Wall-mount bracket
	DH-PFB300C	Celling-mount bracket

Accessories

Optional:



DH-PFA100
Adapting plate






DH-PFB300C
Celling-mount bracket



DH-PFA132-E
Junction Box



DH-PFB302S
Wall-mount bracket

Junction Box	Celling Mount	Wall Mount
PFA132-E	PFB300C+PFA100	PFB302S+PFA100
		

Dimensions (mm/inch)

