

NK-1100



KEY FEATURES

- Remote control of NVRs, network video transmitters, network video receivers and network cameras via network connection
- Control of NVRs by using a USB mouse via network connection
- Two-way audio communication
- Convenient firmware upgrades via either the USB port or ethernet
- Firmware duplication and auto-recovery functions to enhance system stability
- Management of multiple network keyboards via network connection
- Programmable by using the LCD screen

SPECIFICATIONS

COMMUNICATION	
Interface	RS485(Terminal block), Ethernet(RJ45)
Baud Rate	300 bps ~ 115,200bps
Supports Protocols	Over 70 sorts of PTZ protocol (IDIS, PANASONIC, PELCO, SAUMSUNG, etc.)
Supports Devices	IP Camera, NVR, IDIS Solution Suite
Display	LCD(2 Line)
USB	1 port
Audio in/out	1(3.5mm) / 1(3.5mm)
Component	Joystick + Main Control Board
S/W Upgrade	USB, Network
SETUP Program	IDIS Discovery
GENERAL	
Dimension (W x H x D)	376.9mm x 95mm x 177.6mm
Unit Weight	1.1kg
Shipping Dimensions (W x H x D)	455mm x 160mm x 255mm
Shipping Weight	2.1Kg
Power Input	DC 5V, 3A
Certifications	FCC, CE, KC

DA-ES1104



KEY FEATURES

- 19 inch rack-mount type
- Best combination with DirectIP™ NVR
- Supports RAID Levels 0,1+0,5
- SATA to SATA Port Multiplier
- Maximum of 3.0Gbps transfer rate (SATA II)
- Installation of the maximum of four hard disk drives
- Maximised space saving and capacity relative to cost
- Easy expansibility to a very large storage pool

SPECIFICATIONS

HARDWARE	
Interface	eSATA x 1
Number of Drives	SATA II x 4
Drive Size	3.5"
Drive Type	SATA II
PERFORMANCE	
Type and Rate	SATA II(3Gbps)
RAID	0,1+0,5
Max Drive Capacity	12TB(up to 3TB per bay)
GENERAL	
Dimensions (W x H x D)	480mm x 44mm x 346mm
Weight	6.4kg
Operation Temperature	5°C ~ 45°C
Power Input	100V ~ 240VAC, 0.6-0.3A, 50/60Hz
Power Consumption	Max. 40W
Certifications	FCC,CE

