

Datasheet

Instruction

The DNAKE C112 enables you to make the video call with villa entrance door, and open the door remotely from indoor monitor or mobile APP. It also makes an easy integration with SIP devices.

DNAKE C112 (Surface Mounting)



Key Features

- Compact Design
- 2MP, 1080P HD Camera, digital WDR
- H.265 Video Codec
- Motion Detection
- Tamper Alarm
- Optional IC card reader, Wi-Fi
- Support 60,000 cards

Physical

- | | |
|--|---|
| • System: Linux | • Reset Button: 1 |
| • Front Panel: Plastic | • RS485 Port: 1 |
| • Power Supply: PoE (802.3af) or DC 12V/2A | • Relay Out: 1 |
| • Camera: 2MP, CMOS, WDR | • Input: 2 |
| • Indicator Light: 3 | • IP Rating: IP65 |
| • Wiegand Port: Support | • Installation: Surface Mounting |
| • Wi-Fi: IEEE802.11 b/g/n, @2.4GHz (Optional) | • Surface Mounting DIM: 130 x 50 x 28 mm |
| • TF Card Slot: 1 | • Working Temperature: -40°C to +55°C |
| • Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive | • Storage Temperature: -40°C to +70°C |
| • Door Entry: IC (13.56MHz) card (Optional),
Bluetooth (Optional) | • Working Humidity: 10% to 90% (non-condensing) |



Datasheet

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: Built-in speaker

Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Video

- Video Codec: H.264, H.265
- Video Resolution: 1920 x 1080
- Viewing Angle: 110°(H) / 60°(V) / 125°(D)
- Max. Image Transfer Rate: 1080p – 25fps
- Light Compensation: LED white light

