

DH-SD6AL233XA-HNR

2MP 33x Starlight + Laser PTZ AI Network Camera



- 1/1.8" 2Megapixel CMOS
- Powerful 33x optical zoom
- Starlight technology
- Max. 50/60fps@1080P
- Deep-learning-based auto tracking and perimeter protection
- Support Hi-PoE
- Laser distance up to 550 m
- SMD Plus
- IP67



AI series products adopt the most advanced AI technologies, including deep learning algorithms that primarily target people and vehicles, which provides higher flexibility and accuracy for end-users. This enables the Dahua AI series to offer various advanced applications such as Face Recognition, ANPR, Metadata, People Counting, traffic data statistics, etc. The complete lineup of Dahua AI includes network (PTZ) cameras, network video recorders, servers, and more devices. Beyond seeing the world, the power of AI allows devices to perceive the environment and understand the world in a better way.

System Overview

Featuring powerful optical zoom and accurate pan/tilt/zoom performance, this camera provides an all-in-one solution for capturing long distance video surveillance for outdoor applications. Together with infrared illumination and Starlight Technology, the camera is the perfect solution for dark, lowlight applications. The series combines a day/night mechanical IR cut filter for the highest image quality in variable lighting conditions during the day, and True WDR for applications with direct sunlight or glare.

Functions

Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low Light Technology offers best-in-class light sensitivity, capturing color details in low light down to 0.001 lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, True WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Perimeter Protection

Automatically filtering out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improving alarm accuracy.

PFA Technology

PFA technology has innovatively introduced new methods of judgment to ensure the accuracy and predictability of the direction of subject distance adjustment. The result is a set of advanced focusing algorithms. PFA ensures clarity of the image throughout the process of zooming and shortens focus time. The realization of PFA technology substantially improves user experience and increases product value.

SMD Plus

With Deep-Learning Algorithm, Dahua SMD Plus filters the motion detection alarm triggered by non-concerned target and recognizes human and vehicle effectively, sending alarms when human and vehicle intrude.

Technical Specification					Protocol	
					DH-SD Pelco-P/D (auto recognition)	
Camera						
Image Sensor	1/1.8" CMOS					
Max. Resolution	1920 (H) x 1080 (V)					
Effective Pixels	2MP					
ROM	4GB					
RAM	1GB					
Electronic Shutter Speed	1/3–1/30000 s					
Scanning System	Progressive					
Min. Illumination	Color: 0.001Lux@F1.5 B/W: 0.0001Lux@F1.5 0Lux (IR light on)					
IR Distance	550m (1804ft)					
IR On/Off Control	Zoom Prio/Manual/SmartIR					
IR LEDs Number	Laser Module					
Wiper	Support					
Lens						
Focal Length	5.8 mm–191.4 mm					
Max. Aperture	F1.5–F4.8					
Field of View	H: 60.1°–3.2°; V: 35.3° –1.8°; D: 67.9°–3.7°					
Optical Zoom	33x					
Focus Control	Auto/Semi-Auto/Manual					
Close Focus Distance	0.1 m–1 m (0.33 ft–3.28 ft)					
Iris Control	Auto/Manual					
DORI Distance	Detect	Observe	Recognize	Identify		
	1655 m (5429.80ft)	622 m (2040.68ft)	331 m (1085.96ft)	165 m (541.34 ft)		
PTZ						
Pan/Tilt Range	Pan: 0°–360° Tilt: -20°–+90°					
Manual Control Speed	Pan: 0.1°/s–200°/s Tilt: 0.1°/s–120°/s					
Preset Speed	Pan: 240°/s Tilt: 200°/s					
Presets	300					
Tour	8 (up to 32 presets per tour)					
Pattern Number	5					
Scanning Number	5					
Speed Adjustment	Support					
Power-off Memory	Support					
Idle Motion	Preset/Tour/Pattern/Scanning					

Artificial Intelligence	
Video Metadata	Support human, motor vehicle and non-motor vehicle image capture.
Perimeter Protection	Tripwire and intrusion. Support alarm triggering by target types (human and vehicle). Support filtering false alarms caused by animals, rustling leaves, bright lights, etc.
SMD Plus	Support
Auto Tracking	Support
Face Detection	Support
General Intelligence	
Event Trigger	Motion detection, video tampering, scene changing, network disconnection, IP address conflict, illegal access, and storage anomaly.
General IVS	Object Abandoned/Missing
Video	
Compression	H.265/H.265+/H.264+/H.264/MJPEG (sub stream)
Streaming Capability	3 streams
Resolution	1080P (1920 × 1080); 1.3M (1280 × 960); 720P (1280 × 720); D1 (704 × 576/704 × 480); CIF (352 × 288/352 × 240)
Frame Rate	Main stream: 1080P/1.3M/720P (1–50/60fps) Sub stream 1: D1/CIF (1–25/30fps) Sub stream 2: 1080P/1.3M/720P/D1/CIF (1–25/30fps)
Bit Rate Control	Variable Bit Rate/Constant Bit Rate
Bit Rate	H.265/H.264: 3 kbps–20480 kbps
Day/Night	Auto (ICR)/Color/B/W
BLC	Support
WDR	120 dB
HLC	Support
White Balance	Auto/Indoor/Outdoor/Tracking/Manual/Sodium lamp/ Natural light/Street lamp
Gain Control	Auto/Manual
Noise Reduction	2D/3D
Motion Detection	Support
Region of Interest	Support
Electronic Image Stabilization	Support
Defog	Support
Digital Zoom	16x
Flip	0°/180°
Privacy Masking	Up to 24 areas
Audio	
Compression	G.711A; G.711Mu; G.726; AAC; G.722.1; G.723; G.729; PCM; MPEG2-Layer2

Certification	
Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB,ANSI C63.4-2014
Port	
Audio In	1 (LINE IN; bare wire)
Audio Out	1 (LINE OUT; bare wire)
Alarm Port	7/2
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4; IPv6; HTTP; HTTPS; 802.1x; Qos; FTP; SMTP; UPnP; SNMPv1/v2c/v3(MIB-2); DNS; DDNS; NTP; RTSP; RTP; TCP; UDP; IGMP; ICMP; DHCP; PPPoE; ARP; RTCP
Interoperability	ONVIF Profile S&G; CGI
Streaming Method	Unicast/Multicast
User/Host	20 (Total bandwidth 48M)
Edge Storage	FTP; Micro SD card (256G); P2P
Browser	IE7 and newer versions Chrome 42 and older versions Firefox 52 and older versions Safari
Management Software	Smart Player; Smart PSS; DSS; Easy4ip
Smart Phone	IOS/Android
Power	
Power Supply	AC24V/3A±25% Hi-PoE
Power Consumption	20W 33W (Laser on)
Environment	
Operating Temperature	-40°C to +70°C (-40°F to +158°F)
Operating Humidity	≤95%RH
Ingress Protection	IP67; TVS 8000V lightning proof; surge protection
Structure	
Casing	Metal
Dimensions	Φ240 mm x 382 mm (9.45" x 15.04")
Net Weight	6.75 kg (14.88 lb)
Gross Weight	10.1 kg (22.27 lb)

Accessories	PFB303W	Wall Mount
	PFA111	Mount Adapter
	AC24V/3A	Power Adapter
	PFA140	Power Box
	PFB300C	Ceiling Mount
	PFA120	Junction Box
	PFA150	Pole Mount
	PFA151	Corner Mount
	PFB303S	Parapet Mount

Accessories

Included:



PFB303W
Wall Mount



PFA111
Mount Adapter



AC24V/3A
Power Adapter

Optional:



PFA140
Power Box



PFB300C
Ceiling Mount



PFA120
Junction Box



PFA150
Pole Mount




PFA151
Corner Mount



PFB303S
Parapet Mount

Ordering Information		
Type	Model	Description
2MP PTZ Camera	DH-SD6AL233XA-HNR	2MP 33x Starlight+ Laser PTZ AI Network Camera, WDR, PAL
	DH-SD6AL233XAN-HNR	2MP 33x Starlight+ Laser PTZ AI Network Camera, WDR, NTSC
	SD6AL233XA-HNR	2MP 33x Starlight+ Laser PTZ AI Network Camera, WDR, PAL
	SD6AL233XAN-HNR	2MP 33x Starlight+ Laser PTZ AI Network Camera, WDR, NTSC

Ceiling Mount	Junction Mount
PFA111 + PFB300C	PFA111 + PFB303W + PFA120
	
Power Box Mount	Pole Mount
PFA111 + PFB303W + PFA140	PFA111 + PFB303W + PFA150
	
Corner Mount	Parapet Mount
PFA111 + PFB303W + PFA151	PFA111 + PFB303S
