

IR-1100

NEW



- Pre-installed with IDIS Solution Suite VMS
- Tested and validated with IDIS Solution Suite up to 256 Full HD H.264/H.265 IP cameras
- Supports up to 256 Full HD cameras in real-time for enterprise-level surveillance systems
- 1,024Mbps (128MBps) maximum recording bandwidth per server
- Redundancy of power for mission-critical reliability
- Complete compatibility with IDIS components: IP cameras, analog DVR, DirectCX TVR, DirectIP NVR, and encoders
- Equipped with RAID 5, RAID 6 recording, Hot swappable
- 2U rack mount chassis with sliding rails and cable management arm for ease of serviceability
- Supports H.264, H.265 compression, and Intelligent Codec
- Supports Onvif Profile S, Axis, Panasonic, etc.
- NDAA Compliance

SPECIFICATIONS

IR-1100		
SYSTEM	IDIS Solution Suite	Compatible with Expert and Federation Version 2.6.0 or Higher
	Network Connection	4 GbE RJ-45 Ports (1000Base-T)
	Recording Data Rate	Up to 1024Mbps (128MBps)
	Number of Cameras	Up to 256
	Recording Storage	8 Bay
	Hard Disk Drive Configuration	Up to 8 x Large Form Factor Near-line SATA Hard Disk Drives, Hot-swappable, RAID 5, RAID 6
	Operating System	Microsoft® Embedded Windows Server 2016
	Processor	Intel® Xeon® Processor silver 4210 2.2G, 10C/20T
	Memory	8GB RAM (1 x 8GB DDR4-2666MT/s RDIMM)
MECHANICAL	Video Outputs	1 VGA
	Form Factor	2U Rack Mount Chassis
	Dimensions (W x H x D)	482.0mm x 717.6mm x 86.8mm (18.98" x 27.71" x 3.41")
ELECTRICAL	Weight	34.5kg (76 lbs)
	Power Input	100-240V AC, 50/60Hz
	Power Supply	Redundant, Hot Swappable
ENVIRONMENTAL	Power Consumption	750W
	Operating Temperature	10° to 35°C (50° to 95°F)
	Storage Temperature	-40° to 65°C (-40° to 149°F)
	Operating Humidity	10% to 80% Relative Humidity
	Non-operating Humidity	5% to 95% Relative Humidity, 38.7°C (101.7°F) Maximum Wet Bulb Temperature, Non-condensing
	Operating Vibration	0.26 Grms at 5 Hz to 350 Hz
	Storage Vibration	1.88 Grms at 10 Hz to 500 Hz for 15 min
	Operating Shock	Six consecutively executed shock pulses in the positive and negative x, y, and z axes of 6 G for up to 11ms
	Storage Shock	Six consecutively executed shock pulses in the positive and negative x, y, and z axes (one pulse on each side of the system) of 71 G for up to 2 ms
ACCESSORIES SUPPLIED	Operating Altitude	3048m (10,000ft)
	Storage Altitude	12,000 m (39,370 ft)
	Rack Rail System	Sliding rail system with cable management arm. Supports: • Tool-less mounting in 19"-wide EIA-310-E compliant square hole and unthreaded round-hole 4-post racks • Tooled mounting in threaded hole 4-post racks
	Cable	Yes
CERTIFICATIONS	Rack Bezel	1, Front
	Power Cord	1
	FCC Rating Class A	FCC Rating Class A
CERTIFICATIONS	Emissions Classification (EMC)	CISPR 22; EN55022; EN55024; FCC CFR 47; Pt 15; ICES-003; C/NS14336-1; CNS13438; GB4943;GB9254; EN 61000-3-2; EN61000-
	Directives	RoHS, Reach(SVHC), WEEE

ORDERING INFORMATION

Part Number	Description
IR-1100-16TB WS12 DP	IDIS Enterprise NVR, 16TB, RAID5 / Redundant Power Supply with Microsoft Windows Server 2012 and IDIS Solution Suite Expert
IR-1100-32TB WS12 DP	IDIS Enterprise NVR, 32TB, RAID6 / Redundant Power Supply with Microsoft Windows Server 2012 and IDIS Solution Suite Expert
IR-1100-48TB WS12 DP	IDIS Enterprise NVR, 48TB, RAID6 / Redundant Power Supply with Microsoft Windows Server 2012 and IDIS Solution Suite Expert

DIMENSIONS

