

DH-HAC-HDW1200TLMQ(-A)

2MP HDCVI Quick-to-install IR Eyeball Camera



- Max 30fps@1080P
- Quick-to-install eyeball saves installation time
- CVI/CVBS/AHD/TVI switchable
- 3.6mm fixed lens (2.8mm optional)
- Built-in mic(-A)
- Max. IR length 30m, Smart IR
- IP67, DC12V



System Overview

Experience 1080P full HD video and the simplicity of using existing cabling infrastructure with HDCVI. The Lite series 1080P HDCVI camera features a compact design and offers a high quality image at a friendly price. It offers various motorized/fixed lens models with a multi-language OSD and HD/SD switchable output. Its structural flexibility and high cost-performance makes the camera an ideal choice for SMB solutions.

Functions

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the XVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

* Audio input is available for some models of HDCVI cameras.

Easy Installation

HDCVI Quick-to-install eyeball adopts quick-to-install pedestal, which can achieve easier installation than conventional eyeball. Quick-to-install camera reduces time and labor costs.

Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 800m(1080p)/1200m(720P) transmission via coaxial cable, and up to 300m(1080P)/450m(720P) via UTP cable.*

*Actual results verified by real-scene testing in Dahua's test laboratory.

Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Smart IR

The camera is designed with IR LED illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

Multi-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu or by PFM820(UTC controller). This feature makes the camera to be compatible with most end users' existing HD/SD DVRs.

Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments. With working temperature range of -40 °C to +60 °C (-40 °F to +140 °F), the camera is designed for extreme temperature environments. Supporting $\pm 30\%$ input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

Technical Specification							Gain Control		Auto; manual	
Camera							Noise Reduction		2D NR	
Image Sensor		1/2.7 inch CMOS					Smart IR		Yes	
Max. Resolution		1920(H)×1080(V)					Electronic Defog		Yes	
Pixel		2MP					Mirror		Off/On	
Scanning System		Progressive					Privacy Masking		Off/On (8 area, rectangle)	
Electronic Shutter Speed		PAL: 1/25s–1/100000s NTSC: 1/30s–1/100000s					Certifications			
S/N Ratio		>65dB								
Min. Illumination		0.02Lux/F1.9, 30IRE, 0Lux IR on								
Illumination Distance		30 m (98.4 ft)								
Illuminator On/Off Control		Auto; manual								
Illuminator Number		1					Port			
Pan/Tilt/Rotation Range		Pan: 0°–360° Tilt: 0°–78° Rotation: 0°–360°								
Lens										
Lens Type		Fixed-focal								
Mount Type		M12								
Focal Length		2.8 mm; 3.6 mm					Power			
Max. Aperture		F1.9								
Field of View		2.8 mm: 119° x 101° x 54° (diagonal x horizontal x vertical) 3.6 mm: 100° x 84° x 45° (diagonal x horizontal x vertical)								
Iris Type		Fixed iris								
Close Focus Distance		2.8 mm: 0.5 m (1.7 ft) 3.6 mm: 0.8 m (2.6 ft)								
DORI Distance	Lens	Detect	Observe	Recognize	Identify	Environment				
	2.8 mm	38.6 m (126.6 ft)	15.4 m (50.5 ft)	7.7 m (25.3 ft)	3.9 m (12.8 ft)					
	3.6 mm	49.7 m (163.1 ft)	19.9 m (65.3 ft)	9.9 m (32.5 ft)	5 m (16.4 ft)					
Video										
Frame Rate		CVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; AHD: 1080P@25/30fps; 720P@25/30fps; TVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; CVBS: 960H								Structure
Resolution		1080P (1920×1080); 720P (1280×720); 960H (960×576/960×480)								
Day/Night		Auto switch by ICR								
BLC		BLC/HLC/DWDR								
WDR		DWDR								
White Balance		Auto; manual					Casing			
							Camera Dimensions			
							Net Weight			
							Gross Weight			

Ordering Information

Type	Part Number	Description
2MP Camera	DH-HAC-HDW1200TLMQP-A 2.8mm	2MP HDCVI IR Eyeball Camera
	DH-HAC-HDW1200TLMQN-A 2.8mm	
	DH-HAC-HDW1200TLMQP 2.8mm	
	DH-HAC-HDW1200TLMQN 2.8mm	
	DH-HAC-HDW1200TLMQP-A 3.6mm	
	DH-HAC-HDW1200TLMQN-A 3.6mm	
	DH-HAC-HDW1200TLMQP 3.6mm	
	DH-HAC-HDW1200TLMQN 3.6mm	
Accessories	PFA13G	Junction Box
	PFB205W	Wall Mount Bracket (For use alone or with PFA152-E)
	PFA152-E	Pole Mount Bracket (For use with PFB205W)
	PFA130-E	IP66 Junction Box
	PFM800-E	Passive HDCVI Balun
	PFM321D	12V 1A Power Adapter
	PFM820	UTC Controller
	PFM904	Integrated Mount Tester

Accessories

Optional:



PFA13G
Junction Box



PFB205W
Wall Mount Bracket
(For use alone or with
PFA152-E)



PFA152-E
Pole Mount Bracket
(For use with PFB204W)



PFA130-E
IP66 Junction Box



PFM800-E
Passive HDCVI Balun



PFM321D
12V 1A Power Adapter



PFM820
UTC Controller



PFM904
Integrated Mount Tester

Junction Mount	Wall Mount	Ceiling Mount
Pole Mount(Vertical)		

Dimensions (mm[inch])

