

LM22-L200

22" FHD LCD Monitor



Features:

- Industrial level LCD panel, suitable for extensive 24/7 continuous works
- High fidelity digital processing, brilliant and vivid video
- Built in stereo speakers and audio amplifier
- Suitable for every video surveillance and security application, support HDMI, VGA, BNC signal input
- Included desk stand is easily removable for standard VESA mounting
- Support HDCVI, HDTVI, AHD and CVBS 1080P camera display



Technical Specification

Model

Model	LM22-L200
-------	-----------

System

Diagonal	22"(16:9)
Resolution	1920×1080
Backlight	LED
Brightness/Luminance (Standard)	200cd/ m ²
Contrast	1000:1
Angle of View	H170°, V160°
Response Time	5ms
Display Color	8bit(16.7M)
VESA	100×100mm

Interfaces

Input	1 HD(support HDCVI, HDTVI, AHD, CVBS), 1 VGA, 1 HDMI, 1 BNC, 1 Audio	
Output	1 HD (support HDCVI, HDTVI, AHD, CVBS), Built in speakers	
	Speaker	2W×2

General

Consumption (Standard)	≤30W
Consumption (Standby)	≤0.5W
Power Supply	AC100~240V (+/-10%), 50/60 Hz
Gross Weight	5.0kg
Dimensions(no base)	516.60x316.70x51.20mm
Work Environment	Temperature: 0°C~ 40°C
	Humidity: 10%~85%

Accessory

Standard	VGA cable, power cable, pedestal
Optional	Hanging bracket

Dimensions(mm)

