

IPC-HUM8231-L5

2MP Covert Pinhole Network Camera-Lens Unit



- · 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS
- · Day/Night(Electronic), WDR
- · 2.8mm Fixed Pinhole Lens
- · 8-meters cable
- · Require a Main Box to work together







System Overview

Technical Specification

Dahua covert camera used modular design, this product provides an independent miniature sensor unit (with 8-meters cable), while there is a main unit for customers to choose. It can be easily installed into any indoor environments, which makes this camera ideal for the ATMs(Automatic Teller Machines), banks, stores, hotels and offices.

reclinical Specification				
Camera				
Image Sensor	1/2.8" 2Megapixel progressive scan CMOS			
Scanning System	Progressive			
Effective Pixels	1920(H)x1080(V)			
Minimum Illumination	0.02Lux/F2.1 (Color,1/3s,30IRE) 0.1Lux/F2.1 (Color,1/30s,30IRE) 0.01Lux/F2.1 (B/W,1/3s,30IRE) 0.05Lux/F2.1 (B/W,1/30s,30IRE)			
IR Distance	N/A			
IR On/Off Control	N/A			
IR LEDs	N/A			
Lens				
Lens Type	Fixed			
Mount Type	Board-in			
Focal Length	2.8mm			
Max. Aperture	F2.1			
Angle of View	H:111°,V:56°			
Optical Zoom	N/A			
Focus Control	Fixed			
Close Focus Distance	0.6m			
DORI Distance	Detect	Observe	Recognize	Identify
	44m(144ft)	18m(59ft)	9m(29ft)	4m(13ft)

Pan/Tilt/Rotation

Construction

Tany Tity Notation	
Pan/Tilt/Rotation Range	N/A
Certifications	
Certifications	CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B
Environmental	
On anating Conditions	20° C ~ 160° C / 22° E ~ 1140° E\ / Loca +han 0EW BI

Operating Conditions -30° C \sim +60 $^{\circ}$ C (-22 $^{\circ}$ F \sim +140 $^{\circ}$ F) / Less than 95% RH Strorage Conditions -30° C \sim +60 $^{\circ}$ C (-22 $^{\circ}$ F \sim +140 $^{\circ}$ F) / Less than 95% RH Ingress Protection N/A Vandal Resistance N/A

Casing Metal Dimensions 30mm×31mm×32.4mm(1.18"×1.22"×1.28") Net Weight 0.40Kg (0.88lb) Gross Weight 0.47Kg (1.03lb)




Ultra Series | IPC-HUM8231-L5

Ordering Information				
Туре	Part Number	Description		
2MP Camera Lens Unit	IPC-HUM8231-L5	2MP Rectangular Pinhole Lens with 8 meters Cable		
Accessories (Required)	DH-IPC- HUM8231P-E1	2MP Covert Pinhole Network Camera Main Box, PAL		
	DH-IPC- HUM8231N-E1	2MP Covert Pinhole Network Camera Main Box, NTSC		
	IPC-HUM8231P-E1	2MP Covert Pinhole Network Camera Main Box, PAL		
	IPC-HUM8231N-E1	2MP Covert Pinhole Network Camera Main Box, NTSC		
	DH-IPC- HUM8231P-E2	2x2MP Covert Pinhole Network Camera Main Box, PAL		
	DH-IPC- HUM8231N-E2	2x2MP Covert Pinhole Network Camera Main Box, NTSC		
	IPC-HUM8231P-E2	2x2MP Covert Pinhole Network Camera Main Box, PAL		
	IPC-HUM8231N-E2	2x2MP Covert Pinhole Network Camera Main Box, NTSC		

<u>Link: http://www.dahuasecurity.com/products_category/2-megapixel-4271.html</u>

Installation



Dimensions (mm/inch)

