



JC-D1080V-212


КУПОЛЬНАЯ ВИДЕОКАМЕРА 1080P
СТАНДАРТА AHD



ОСОБЕННОСТИ

- Матрица 1/2.9" CMOS SONY IMX322 2.2 Мп
- Процессор NVP2441H
- Разрешение HD 1080P (1920x1080)
- Объектив вариофокальный 2,8~12 мм
- Угол обзора по горизонтали 90°~22°
- Функции ATW, DSS, BLC, AGC, 3DNR, D-WDR, De-Fog
- Температурный режим от -10°C до +40°C
- Питание DC12V $\pm$ 10%
- Защита от неправильной полярности (переплюсовки)
- Низкое энергопотребление

РАЗМЕРЫ



ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

IP Rating	IP55
Image Sensor	1/2.9" 2.2 Mega Pixels SONY CMOS
Pixels	1920(H)X1080(V)
Horizontal Resolution	1080P
Viewing Angle	Horizontal: 90° ~22°
Minimum Lux	0.0001Lux (Sense-up ON)
Vertical Frequency	NTSC:60Hz PAL:50Hz
Horizontal Frequency	NTSC:15.734KHz PAL:15.625KHz
Scanning System	Progressive
S/N Ratio	≥52dB
Electronic Shutter	NTSC:1/60-1/100,000S PAL:1/50-1/100,000S
Lens	2.8~ 12 mm Varifocal Lens
White Balance	ATW
OSD	YES
BackLight Compensation	AUTO
AUTO Gain Control	ON
Defog	OFF/ON
DNR	OFF/ON
WDR	OFF/ON
Day&Night	AUTO/Color/BW/Ext
Gamma	0.45
Video Output	HD-AHD(1080P)/ CVBS
Power Supply	DC12V/55mA±6mA (wide voltage:9V-18V)
Current consumption	300mA (MAX)
Dimension	ø112x87mm (4.41"x3.42")
Weight	170g (5.99oz)
Storage Temperature	-30℃ — +60℃
Operating Temperature	-10℃ — +40℃