

DH-IPC-HDBW5541E-Z5E

5MP Pro AI IR Vari-focal Dome Network Camera



System Overview

Pro AI series contains Face Detection, Perimeter Protection and People Counting functions. Powered by deep-learning Artificial Intelligence algorithms, significantly improved accuracy. Meanwhile, the series features starlight and smart IR technology. This series fully protected from dust and water, certified to IP67 and vandal resistant to IK10 standard.

Functions

Face Detection

Face Detection is a software application that automatically captures faces from within a digital image or a video frame from a video source. Dahua cameras use advanced deep learning algorithms and are trained by a large number of face data sources, enabling the camera to locate faces quickly and accurately from the video source and capture facial images.

Face Attributes

Through the use of deep learning algorithms to analyze facial images, Dahua cameras can extract six facial attributes from each frame, including Age, Gender, Expression (Jolly/Surprise/Normal/Rage/Sad/Disgusted/Confused/Frightened), Glasses, Mouth Mask, Moustache & Beard. Customers can acquire data of interest via face attributes statistics.

Perimeter Protection

Dahua's Perimeter Protection functions significantly improved accuracy. Perimeter Protection reduces false alarms and decreases pixel count requirements for object detection. Perimeter Protection features custom tripwires based on object type for automation in limited access areas such as pedestrian or vehicle-only zones. This combination of advanced AI analytics and real-time alerts to a desktop or to a mobile client reduces system requirements and resources resulting in greater surveillance system efficiency.

- 1/2.7" 5Megapixel progressive scan CMOS
- H.265 & H.264 triple-stream encoding
- 20 fps@2592 × 1944, 50/60 fps@1080P (1920 × 1080)
- WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS
- 7 mm–35 mm motorized lens
- 1/1 Alarm in/out, 1/1 audio in/out
- Max. IR LEDs Length 80 m
- Micro SD memory, IP67, IK10



People Counting

People Counting function uses advanced image processing technology to capture depth information from within images. The camera pairs this information with deep learning algorithms to analyze and detect human bodies and track target objects in real time. The camera provides statistics for separate individuals' entrance and exit with up to 95% counting accuracy.

Metadata

Metadata is feature attribute information extracted from a target object which can be used for data retrieval. Dahua face detection camera can extract six facial attributes and output the metadata for analysis.

ePoE technology

The ePoE technology of Dahua, designed internally, adopts advanced 2D-PAM3 coding modulation from physical layer, and realizes full duplex transmission over 800 meters at the speed of 10Mbps, or 300 meters at the speed of 100Mbps via Cat 5 or coaxial cable media. Besides, it supports PoE and PoC power supply technology which has greatly simplified construction and wiring. Dahua ePoE technology offer a new way to accomplish long distance transmission between IP camera and network switch. It allows more flexible surveillance system design, improves reliability and saves construction and wiring cost.

Protection(IP67, IK10, wide voltage)

The camera allows for $\pm 30\%$ input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 6KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67) and impact tests (IK10), the camera is the choice for installation in even the most unforgiving environments.

Technical Specification					
Camera					
Image Sensor		1/2.7" 5Megapixel progressive scan CMOS			
Effective Pixels		2592 (H) × 1944 (V)			
RAM/ROM		1 GB/128 MB			
Scanning System		Progressive			
Electronic Shutter Speed		Auto/Manual, 1/3 s–1/100000 s			
Minimum Illumination		0.003 Lux@F1.3			
IR Distance		Distance up to 80 m (262 ft)			
IR On/Off Control		Auto/Manual			
IR LEDs		3			
Lens					
Lens Type		Motorized vari-focal			
Mount Type		Board-in			
Focal Length		7 mm–35 mm			
Max. Aperture		F1.3			
Angle of View		H: 31°–9°, V: 23°–7° (2592 × 1944) H: 32°–9°, V: 18°–5° (2688 × 1520)			
Aperture Type		Auto (HALL)			
Close Focus Distance		0.4 m–2.0 m (1.31 ft–6.56 ft)			
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	W	190m(623ft)	76m(249ft)	38m(125ft)	19m(62ft)
	T	620m(2034ft)	248m(814ft)	124m(407ft)	62m(203ft)
Pan/Tilt/Rotation					
Pan/Tilt/Rotation Range		Pan: 0°–355°; Tilt: 0°–65°; Rotation: 0°–355°			
Artificial Intelligence					
Face Detection		Support face image capture			
Face Attributes		Support 6 kinds of face attributes extraction: Age, Gender, Expression (Jolly, Surprise, Normal, Rage, Sad, Disgusted, Confused, Frightened), Glasses, Mouth Mask, Moustache & Beard			
Perimeter Protection		Tripwire, intrusion (Recognition of vehicle and people), fast moving, loitering detection, parking detection and people gathering			
People Counting		Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas independent detection			
General Intelligence					
Event Trigger		Motion detection, Video tampering , Scene changing, Network disconnection , IP address conflict, Illegal Access,Storage anomaly			
General Intelligence		Object Abandoned/Missing			
Heat Map		Yes			
Video					
Compression		H.265,H.264,H.264B,H.264H, MJPEG (sub stream)			

Smart Codec	Yes
Streaming Capability	3 Streams
Resolution	2592 × 1944/2688 × 1520/2560 × 1440/2304 × 1296/1080P (1920 × 1080)/1.3M (1280 × 960)/720P (1280 × 720)/D1 (704 × 576/704 × 480)/VGA (640 × 480)/CIF (352 × 288/352 × 240)
Frame Rate	Main Stream: 2592 × 1944 (1 fps–20 fps) 2560 × 1440 (1 fps–25/30 fps) 1920 × 1080 (1 fps–50/60 fps) Sub Stream: D1 (1 fps–20/30 fps) D1 (1 fps–50 fps) Third Stream: 1080P (1 fps–17 fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.264: 32 Kbps–8192 Kbps H.265: 19 Kbps–8192 Kbps
Day/Night	Auto(ICR)/Color/B/W
BLC Mode	BLC/HLC/WDR (120 dB)
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detection	Off/On (4 Zone, Rectangle)
Region of Interest	Off/On (4 Zone)
Electronic Image Stabilization (EIS)	Yes
Smart IR	Yes
Defog	Yes
Flip	0°/90°/180°/270°
Mirror	Off/On
Privacy Masking	Off/On (4 Area, Rectangle)
Audio	
Compression	G.711a, G.711Mu, G.726, AAC, G.723
Network	
Ethernet	RJ-45 (10/100 Base-T)
Protocol	IPv4;IPv6;HTTP;HTTPS;TCP;UDP;ARP;RTP;RTSP;RTCP ;RTMP;SMTP;FTP;SFTP;DHCP;DNS;DDNS;QoS;UPnP ;NTP;Multicast;ICMP;IGMP;NFS;PPPoE;802.1x;SNMP
Interoperability	ONVIF (Profile S/Profile G/Profile T), CGI, Milstone, Genetec, P2P
Streaming Method	Unicast/Multicast
Max. User Access	20 Users
Edge Storage	NAS;FTP;SFTP Micro SD card 256 GB
Web Viewer	IE (versions newer than IE8), Chrome, Firefox, Safari (versions newer than Safari 12)
Management Software	Smart PSS, DSS, DMSS
Smart Phone	iOS, Android
Certifications	

Certifications	CE-LVD: EN60950-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07
----------------	--

Interface

Audio Interface	1/1 channel In/Out
RS485	N/A
Alarm	1 channel In: 5mA 5V DC 1 channel Out: 300mA 12V DC

Electrical

Power Supply	DC 12V ($\pm 30\%$), AC 24V ($\pm 30\%$), PoE (802.3af) (Class 0)
Power Consumption	<12.4W

Environmental

Operating Conditions	-30° C to +60° C (-22° F to +140° F)/Less than 95% RH
Storage Conditions	-30° C to +60° C (-22° F to +140° F)
Ingress Protection	IP67
Vandal Resistance	IK10

Construction

Casing	Metal
Dimensions	$\Phi 159.0 \text{ mm} \times 117.9 \text{ mm}$ (6.26" $\times$ 4.64")
Net Weight	0.95 kg (2.09 lb)
Gross Weight	1.20 kg (2.65 lb)

Ordering Information

Type	Part Number	Description
5MP camera	DH-IPC-HDBW5541EP-Z5E	5MP Pro AI IR Vari-focal Dome Network Camera, PAL
	DH-IPC-HDBW5541EN-Z5E	5MP Pro AI IR Vari-focal Dome Network Camera, NTSC
	IPC-HDBW5541EP-Z5E	5MP Pro AI IR Vari-focal Dome Network Camera, PAL
	IPC-HDBW5541EN-Z5E	5MP Pro AI IR Vari-focal Dome Network Camera, NTSC
Accessories (optional)	PFA138	Junction Box
	PFB210W	Wall mount
	PFB300C	Ceiling mount
	PFA152-E	Pole mount
	PFA101	Mount adapter
	PFB201C	In-ceiling mount

Accessories

Optional:



In-ceiling Mount	Junction Mount	Pole Mount
PFB201C	PFA138	PFB210W + PFA152-E
Ceiling Mount	Wall Mount	
PFA101 + PFB300C	PFB210W(Indoor)	PFB210W(Outdoor)

Dimensions (mm[inch])

