

DH-PFM320S-150

DC12V 150W Switching Power Supply




Features

- 88~132Vac/176~264Vac wide-range voltage input, meet the requirements in different parts for electric network fluctuation;
- Support supply power to multi-channel cameras simultaneously to meet the demand of different loads for power supply;
- Support the output voltage adjustable: can adjust the output resistance to select the right output voltage ($\pm 10\%$) for different loads, which is flexible in field applications;
- High quality and reliability: Pass 3 months high temperature aging test.


Technical Specification	
Model	DH-PFM320S-150
Electrical Specification	
Input Voltage Range	88~132Vac/176~264Vac
Efficiency	85.0% (@230Vac)
Output Voltage	12Vdc (terminal output)
Out Voltage Tolerance	±5%
Adjustable Range for DC Voltage	±10% (10.8Vdc~13.2Vdc)
Rated Output Current	12.5A
Output Power	150W
No Load Power Consumption	<0.5W
Protection/Environmental	
Surge Protected	Line to ground: ±2000V Line to line: ±1000V
ESD	Contact discharge: ±6000V Air discharge: ±8000V
Working Temperature	-20℃~+50℃ (60% output at +70℃) -4℉~+122℉ (60% output at +158℉)
Working Humidity	<90% RH
Physical Properties	
Weight	0.4kg(0.88lb)
Dimension(LxWxH)	159mmx97mmx30mm (6.26"x3.82"x1.18")
Installation	Wall mount/Ceiling mount
Color	Metallic silver
Safety Standards	
Certification	CE, FCC

Ordering Information		
Type	Part Number	Description
Power series	DH-PFM320S-50	DC12V 50W switching power supply
	DH-PFM320S-150	DC12V 150W switching power supply
	DH-PFM321S-75	DC24V 75W switching power supply

Dimensions (mm/inch)



Application



Package Information

- DC12V 150W switching power supply DH-PFM320S-150 *1
- User manual *1