

DHL32

32" Full-HD LCD Monitor



Features :

- Industrial level DID LCD panel, suitable for extensive 7×24 continuous works
- FHD 1920×1080 resolution, brilliant and vivid video
- Abundant interfaces, support video loop
- Remote control, software dual control, support remote PC centralized control
- Using tamper-proof metal housing, no radiation
- Professional thermal design to extend equipment lifespan



Technical Specification

Model

Model	DHL32
-------	-------

System

Diagonal	32"(16:9)
Resolution	1920×1080
Backlight	LED
Brightness/Luminance (Standard)	350 cd/ m ²
Contrast	1200:1
Angle of View	178°/178°(vertical/horizontal)
Response Time	8ms
Display Color	16.7M

Signals

Input	Standard	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1
	Optional	Audio×1
Output	Standard	CVBS(BNC)×2, RS232×1
	Optional	DP×1

General

Consumption (Standard)	35W
Consumption (Standby)	0.5W

Power Supply	AC100~240V (+/-10%), 50/60 Hz
Weight	9.0kg
Dimensions(no base)	750.7×455.1×44.0(mm)
Work Environment	Temperature: 0 C~50 C
	Humidity: 10%~80%

Dimensions(mm)

