



Features

- 1/3 inch Sony Exview HAD CCD
- High Resolution : 580 TV Lines
- Min Illumination : 0.002 Lux (AGC High, Exview CCD)
- AGC (High/Low)
- BLC, Flickerless (On/Off)



REAR VIEW



DIMENSIONS

SPECIFICATIONS

Model	CNB-G3010NBX	CNB-G3010PBX
Signal System	EIA	CCIR
Scanning System	2:1 Interface	
Sync. System	Internal	
Image Sensor	1/3 Inch SONY Exview CCD	
Total Pixels	811(H) x 508(V) 410K	795(H) x 596(V) 470K
Effective Pixels	768(H) x 494(V) 380K	752(H) x 582(V) 440K
Horizontal Resolution	580 TV Lines	
Lens Mount	C/CS Mount	
Video Output	Composite: 1.0V p-p, 75Ω, Unbalanced	
S/N Ratio	More than 46dB(AGC Off)	
Min. Illumination	0.002 Lux (F1.2, AGC High)	
AGC	Function (Low/High)	
BLC	On(Center + Lower portion measured)/Off	
Flickerless	On/Off	
IRIS	Electronic Auto ~ Iris (EE) Mechanical Auto-Iris(DC/Video)	
Gamma Characteristic	0.45	
Shutter Speed	EL : 1/60~100,000 FL : 1/1100 sec. Fixed OFF : 1/60 sec. Fixed	EL : 1/50~1/100,000 FL : 1/120 sec. Fixed OFF : 1/50 sec. Fixed
Operating Temperature	-10°C ~ +50°C (Recommendation : -5°C ~ +40°C)	
Supplied Voltage	DC 8V~15V (Recommendation 12V±0.5V)	
Power Consumption	Max. 100mA/1.2W	
Dimensions	63.5(W) x 55.6(H)x71.9(D) mm	
Weight	300g	