

## AiS- 22 -31N1W



### Feature:

- High resolution, image presented vivid and clear
- Support automatic color change/IR-CUT, achieving day and night non-stop monitoring
- Support various information superimposed
- Support 2D / 3D noise reduction, digital wide dynamic function
- 
- 
- support all types of mobile remote monitoring (iOS, Windows Mobile, BlackBerry, Symbian, Android);
- Multi-browser access (IE, Chrome, Firefox, Safari);
- Support web, CMS, center platform management software MYEYE, provide SDK Development.

### Model:

AiS-Z22K-31N1W

### Parameters:

Model	<b>AiS-Z22K-31N1W</b>
<b>Network camera</b>	
Sensor	1/2.8" SONY IMX222 ultra-low illumination CMOS
Minimum illumination	Color 0.01Lux @(F1.2,AGC ON),0 LUX with IR Black & White 0.001 Lux @ (F1.2,AGC ON),0 LUX with IR
Shutter	1/50(1/60)s to 1/10,000s
Lens	HD professional lens 3.6mm
Lens Interface	M12
Day and night	Support IR-CUT
<b>Compression Standard</b>	
Video	H.264 High Profile, PE snapshot
output rate	100Kbps~8Mbps
audio	G.711a
<b>Image</b>	
Max. image size	1920*1080
Frame Rate	50Hz:25fps (1920*1080)/(1280*720) 60Hz:30fps (1920*1080)/(1280*720)
Image Settings	Saturation, brightness and contrast can be adjusted through IE or Client
<b>Network functions</b>	
Storage	twor stora
WIFI	No
Intelligent Alarm	Motion detection, video loss, cable break, IP address conflict
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,PPPoE,SMTP,NTP(HTTPS,SIP,802.1x,IPv6Optional )
Other	Anti-flicker, dual-stream, heartbeat, password protection
<b>Interface</b>	
Communication	1*RJ45 10M/100M
<b>General Specifications</b>	
temperature and humidity	-65℃~65℃, humidity less than 90% (non-condensing)
Power supply	DC12V±10%
Protection class	IP67
Dimension	Φ93mm*68mm
Weight	300g