

## AiS-D22V-55N1W



### Feature:

- High resolution, image presented vivid and clear
- Support automatic color change/IR-CUT, achieving day and night non-stop monitoring
- Support various information superimposed
- Support 2D / 3D noise reduction, digital wide dynamic function
- Excellent AF algorithm
- Support POE function
- support all types of mobile remote monitoring (iOS, Windows Mobile, BlackBerry, Symbian, Android);
- Multi-browser access (IE, Chrome, Firefox, Safari);
- Support web, CMS, center platform management software MYEYE, provide SDK Development.
- Smoked cover supported

### Model:

AiS-D22V-55N1W

### Parameters:

|                               |   |
|-------------------------------|---|
| Model                         | AiS-D22V-55N1W  |
| <b>Network camera</b>         |   |
| Sensor                        | 1/2.8" SONY IMX222 ultra-low illumination CMOS  |
| Minimum illumination          | Color 0.01Lux @(F1.2,AGC ON),0 LUX with IR<br>Black & White 0.001 Lux @ (F1.2,AGC ON),0 LUX with IR |
| Shutter                       | 1/50(1/60)s to 1/10,000s  |
| Lens                          | 2.8mm-12mm HD automatically zoom lens<br>Angle of View (H): 100.0° (wide) ~30° (tele)               |
| Lens Interface                | M14   |
| Day and night                 | Support IR-CUT  |
| <b>Compression Standard</b>   |   |
| Video                         | H.265/H.264,dual stream, AVI; 1~30f/s variable  |
| output rate                   | 32 Kbps~8Mbps   |
| audio                         | G.711a  |
| <b>Image</b>                  |   |
| Max. image size               | 1920*1080   |
| Frame Rate                    | 50Hz:25fps (1920*1080),(704*576)<br>60Hz:30fps (1920*1080),(704*480)                                |
| Image Settings                | Saturation, brightness and contrast can be adjusted through IE or Client                            |
| <b>Network functions</b>      |   |
| Storage                       | No  |
| WIFI                          | No  |
| Intelligent Alarm             | Motion detection, video loss, cable break, IP address conflict                                      |
| Protocol                      | TCP/IP,HTTP,DHCP,DNS,DDNS,PPPoE,SMTP,NTP(HTTPS,SIP,802.1x,IPv6Optional )                            |
| Other                         | Anti-flicker, dual-stream, heartbeat, password protection   |
| <b>Interface</b>              |   |
| Communication                 | 1*RJ45 10M/100M   |
| <b>General Specifications</b> |   |
| temperature and humidity      | -65°C~65°C, humidity less than 90% (non-condensing)   |
| Power supply                  | DC12V±10%   |
| Protection class              | IP67  |
| Dimension                     | 137mm*103mm   |
| Weight                        | 635 g   |