

DS-PM1-RT-HWE 868MHz Tri-X Wireless Receiver



Tri-X wireless receiver, compatible with AX Hybrid Pro control panel, used to expand wireless capability of the control panel. HIKVISION Tri-X detectors can be added to AX Hybrid Pro panel via this wireless receiver.

- 868MHz wireless receiver
- Wireless transmission distance up to 1700m
- Supports 32 wireless detectors, 4 wireless indoor sounders and 8 wireless outdoor sounders

▪ Specification

Hardware features	
Bus	1 Speed-X bus
Electrical characteristics	
Power supply	9 to 28 VDC, 1A
Power consumption	Maximum current 100 mA@12 VDC; Quiescent current 40 mA@12 VDC
Wireless transmission	
RF frequency	868 MHz
Wireless security	Frequency hopping 128 AES encryption
Display	
LED Indicator	1. Green: power/find me 2. Orange: alarm/fault
General	
Dimension(WxHxD)	110 mm × 155 mm × 32 mm
Shell material	Plastic
Weight	225 g
Operation temperature	-10°C to 40°C
Operation humidity	10% to 90%
Device management	
Alarm input	Up to 32 wireless detectors(portable emergency button is not included)
Wireless sounder	Up to 4 wireless indoor sounder, 8 wireless outdoor sounder

▪ Available Model

DS-PM1-RT-HWE

Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
+86-571-8807-5008
www.hikvision.com



Follow us on social media to get the latest product and solution information:



HIKVISION



HIKVISION



HIKVISION



HIKVISION



HIKVISION
Corporate Channel



HIKVISION