

PFM809-4MP

16 Channel Passive HDCVI Balun



Features

- Power supply: No need additional power supply.
- Transmission effect: Real-time transmission HDCVI/AHD/TVI/CVBS video signal without compression, video is clear and stable.
- Transmission distance: 0~400m (with passive transmitter).
- Main functions: Use 4 wires meanwhile to transmit 16-ch video signal.
- Protection and anti-interference: Excellent anti-thunder, anti-static and anti-interference capabilities.
- Appearance structure: BNC coaxial interface, the green has screw terminal and crystal head twisted-pair cable interface.


Technical Specifications


Model	PFM809-4MP
Properties	
Transmission Signal	16 channel
Transmission Distance	HDCVI: 720P: max.400m(1312.34ft); 1080P: max. 250m(820.21ft); 4MP: max. 200m(656.17ft)
Category Type	UTP CAT5E/6
Video Transmission Properties And Port	
Coaxial Video Connector	BNC
Connection Way	Spring loaded
Compatible Format	HDCVI/AHD/TVI/CVBS
Resolution	720P/1080P/4MP
Anti-interference	>60db
Protection	
ESD	1a contact discharge electricity level 3
	1b air discharge electricity level 3
	Per: IEC61000-4-2
Coaxial Cable Connector	2KV(common-code)
	Per: IEC61000-4-5
UTP Cable Connector	2KV(different-code), 4KV(common-code)
	Per: IEC61000-4-5
Impedance	
BNC Male	75 ohms
UTP Cable	100 ohms
Physical Properties	
Dimension(L*W*H)	430mm*100mm*44.5mm(1U) (16.93"x3.94"x1.75")
Shell	SECC
Color	Black
N.W.	1.25kg(2.76lb)
Stability	
MTBF	>10000H
Environmental	
Operating Temperature	-10℃~+55℃(14°F~131°F)
Storage Temperature	-20℃~+70℃(-4°F~158°F)
Humidity	0~95%(non-condensing)
Certification	
Certification	CE, FCC

Order Information

Type	Part Number	Description
Balun	PFM809-4MP	16 channel passive HDCVI Balun
Related Accessory	DH-PFM920	305m UTP CAT5E cable _Dahua brand; Bare stranded copper conductor
	PFM920	305m UTP CAT5E cable _Neutral, no brand; Bare stranded copper conductor
	DH-PFM921	305m UTP CAT6 cable _Dahua brand; Bare stranded copper conductor
	PFM921	305m UTP CAT6 cable _Neutral, no brand; Bare stranded copper conductor
	DH-PFM922	305m UTP CAT6 cable _Dahua brand, copper clad aluminum conductor
	PFM922	305m UTP CAT6 cable _Neutral, no brand; Copper clad aluminum conductor

Dimensions (mm/inch)





Package Information

- 1 Channel Passive HDCVI Balun PFM809-4MP *1
- Application manual *1
- Round foot mat *4
- Rack-mounting ear *2
- Rack-mount screws *8
- Desiccant *1