

DS-WSELI-T/P Series Workstation



Introduction


Embedded with the Linux operating system, the DS-WSELI-T/P Series Workstation provides well performance in CPU processing, decoding, and storage capability. It allows the integration of the Hikvision hardware and the third-party VMS software to maintain a flexible one-stop solution.

The DS-WSELI-T/P workstation can be applied to the small-scale chain management with convenient remote centralized storage.

Key Feature

- High stability and reliability
- Compact and flexible structure design
- Linux operating system
- Various CPU / memory options selectable
- Allow installing or integrating with the third-party VMS software
- mSATA SSD available for operating system and software installation
- 2 HDMI outputs at up to 4K resolution
- 8/16 independent PoE network interfaces are provided


Typical Application



Specifications

Model		DS-WSELI-T2/8P	DS-WSELI-T4/16P
System	Processor	Intel® Celeron® Processor J3455 (2M Cache, up to 2.3 GHz), 64 bit, 4 Core	
	Memory	DDR3L, 4GB	
	Graphics card	Intel® HD Graphics 500	
	Operating system	Ubuntu Linux 16.04	
Storage	System disk (OS, VMS)	mSATA 32GB	
		Optional: mSATA 64GB	
	SATA interface	2 SATA interfaces	4 SATA interfaces
		1TB/2TB/3TB/4TB/5TB/6TB/8TB/10TB capacity for each disk	
Video/Audio output	HDMI interface	2 ×HDMI interface	
		4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
	VGA interface	1 × VGA interface	
		1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
	Audio input	1-ch, 3.5 mm audio connector	
External interface	Audio output	1-ch, 3.5 mm audio connector	
	LAN	2 × RJ45 10M/100M/1000M self-adaptive Ethernet interface	
	USB interface	Front panel: 2 × USB 2.0; Rear panel: 4 × USB 3.0	
	Serial interface	RS-232; RS-485	
POE Interface	Alarm input / output	4/2	16/4
	Interface	8 RJ-45 10/100 Mbps self-adaptive Ethernet interfaces	16 RJ-45 10/100 Mbps self-adaptive Ethernet interfaces
	Output power	≤ 120 W	≤ 150 W
	Supported standard	IEEE 802.3 af/at	
General	Power supply	100 to 240 VAC, 50 to 60 Hz	
	Consumption (without hard disk)	≤ 30 W	
	Working temperature	0 to +45° C (+32 to +113° F)	
	Working humidity	10 to 90 % (Non-condensing)	
	Chassis	19-inch rack-mounted 1U chassis	19-inch rack-mounted 1.5U chassis
	Dimensions (W × D × H)	445 × 290 × 45 mm (17.5" × 11.4" × 1.8")	445 × 400 × 71 mm (17.5"× 15.7" × 2.8")
	Weight (without hard disk)	≤ 3 kg (6.6 lb)	≤ 5 kg (11 lb)

Physical Interfaces



Index	Description	Index	Description
1	RS-232 Serial Interface	7	RS-485 Serial Interface, Terminal Switch
2	VGA Output Interface	8	Alarm Input / Output
3	LAN1 and LAN2 Interfaces	9	GND
4	Audio Input / Output Interface	10	100 to 240 VAC power supply
5	HDMI1 and HDMI2 Interfaces	11	Power Switch
6	4 × USB 3.0 Interface	12	PoE interface (8 interfaces for 8P and 16 interfaces for 16P)

Available Models

DS-WSELI-T2/8P, DS-WSELI-T4/16P

Distributed by



HIKVISION

Headquarters

No.325 Dianming Road, Binyang District,
Hangzhou 310051, China
T: +86-571-8007-5960
overseasbusiness@hikvision.com

Hikvision USA
T: +1-800-835-0400
sales.usa@hikvision.com

Hikvision Australia
T: +61-2-8589-4233
sales.au@hikvision.com

Hikvision India
T: +91-22-28468900
sales@oceanhikvision.com

Hikvision Canada
T: +1-888-203-6600
sales.canada@hikvision.com

Hikvision Thailand
T: +662-214-8848
sales.thailand@hikvision.com

Hikvision Europe
T: +31-20-5642770
sales.eu@hikvision.com

Hikvision Italy
T: +39-0438-66007
info.it@hikvision.com

Hikvision Brazil
T: +55-11-3119-0050
latam.support@hikvision.com

Hikvision Turkey
T: +90-216-521-7070-7074
sales.tr@hikvision.com

Hikvision Malaysia
T: +601-7687-2411
sales.my@hikvision.com

Hikvision UK & Ireland
T: +44-208-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27-210-2351172
sales.africa@hikvision.com

Hikvision France
T: +33-101-05-550-550
info.fr@hikvision.com

Hikvision Kazakhstan
T: +7-727-5750957
asia.pacific@hikvision.ru

Hikvision Vietnam
T: +84-234778888
sales.vn@hikvision.com

Hikvision UAE
T: +971-4-4432080
sales.me@hikvision.com

Hikvision Singapore
T: +65-6594-4216
sg@hikvision.com

Hikvision Spain
T: +34-91-737-18-56
info.es@hikvision.com

Hikvision Tashkent
T: +99-87-1276-8439
uzb@hikvision.ru

Hikvision Hong Kong
T: +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T: +7-495-658-67-99
sales.ru@hikvision.com

Hikvision Korea
T: +82-1031-731-6817
sales.korea@hikvision.com

Hikvision Poland
T: +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T: +62-21-2033759
sales.indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com