

DS-WSELI-T Series Workstation




Introduction

Embedded with the Linux operating system, the DS-WSELI-T Series Workstation provides well performance in CPU processing, decoding, and storage capability. It allows the integration of the Hikvision hardware and the third-party VMS software to maintain a flexible one-stop solution. The DS-WSELI-T workstation can be applied to the small-scale chain management with convenient remote centralized storage.

Key Feature

- High stability and reliability
- Compact and flexible structure design
- Linux operating system
- Various CPU/memory options selectable
- Allow installing or integrating with the third-party VMS software
- mSATA SSD available for operating system and software installation
- 2 HDMI outputs at up to 4K resolution


Typical Application



Specifications

Model		DS-WSELI-T2	DS-WSELI-T4
System	Processor	Intel® Celeron® Processor J3455 (2M Cache, up to 2.3 GHz), 64 bit, 4 Core;	
	Memory	DDR3L, 4GB	
	Graphics card	Intel® HD Graphics 500	
	Operating system	Ubuntu Linux 16.04	
Storage	System disk (OS, VMS)	mSATA 32GB	
		Optional: mSATA 64GB	
	SATA interface	2 SATA interfaces	4 SATA interfaces
Video/Audio output	HDMI interface	2 × HDMI interface	
		4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
	VGA interface	1 × VGA interface	
		1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
	Audio input	1-ch, 3.5 mm audio connector	
	Audio output	1-ch, 3.5 mm audio connector	
External interface	LAN	2 × RJ45 10M/100M/1000M self-adaptive Ethernet interface	
	USB interface	Front panel: 2 × USB 2.0; Rear panel: 4 × USB 3.0	
	Serial interface	RS-232; RS-485	
	Alarm Input / Output	4/2	16/4
General	Power supply	100 to 240 VAC, 50 to 60 Hz	
	Consumption (without hard disk)	≤ 30 W	
	Working temperature	0 to +45° C (+32 to +113° F)	
	Working humidity	10 to 90 % (Non-condensing)	
	Chassis	19-inch rack-mounted 1U chassis	19-inch rack-mounted 1.5U chassis
	Dimensions (W × D × H)	445 × 290 × 45 mm (17.5" × 11.4" × 1.8")	445 × 400 × 71 mm (17.5" × 15.7" × 2.8")
	Weight (without hard disk)	≤ 3 kg (6.6 lb)	≤ 5 kg (11 lb)

Physical Interfaces



Index	Description	Index	Description
1	RS-232 Serial Interface	7	RS-485 Serial Interface, Terminal Switch
2	VGA Output Interface	8	Alarm Input / Output
3	LAN1 and LAN2 Interfaces	9	GND
4	Audio Input / Output Interface	10	100 to 240 VAC power supply
5	HDMI1 and HDMI2 Interfaces	11	Power Switch
6	4 x USB 3.0 Interface		

Available Models

DS-WSELI-T2, DS-WSELI-T4

Designed by



HIKVISION

Headquarters

No.325 Vienna Road, Binyang District,
Hangzhou 310051, China
T +86-571-8007-5960
overseas@ Hikvision.com

Hikvision USA
T +1 800 895 0400
sales.usa@ Hikvision.com

Hikvision Australia
T +61 2 9299 4232
sales.au@ Hikvision.com

Hikvision India
T +91 22 28466603
sales@ Hikvision.in

Hikvision Canada
T +1 888 700 6800
sales.canada@ Hikvision.com

Hikvision Thailand
T +66 2 215 8846
sales.thailand@ Hikvision.com

Hikvision Europe
T +31 20 3642770
sales.eu@ Hikvision.com

Hikvision Italy
T +39 0438 82007
info.it@ Hikvision.com

Hikvision Brazil
T +55 11 3118 3000
letam.support@ Hikvision.com

Hikvision Turkey
T +90 210 521 7070-7074
sales.tr@ Hikvision.com

Hikvision Malaysia
T +60 3 7857 2411
sales.my@ Hikvision.com

Hikvision UK & Ireland
T +44 208 902140
sales.uk@ Hikvision.com

Hikvision South Africa
T +27 10 1351132
sales.africa@ Hikvision.com

Hikvision France
T +33 01 61 330 450
info.fr@ Hikvision.com

Hikvision Kazakhstan
T +7 727 5750067
sales.pandflow@ Hikvision.ru

Hikvision Vietnam
T +84 074770885
sales.vn@ Hikvision.com

Hikvision UAE
T +971 4 4432060
sales.me@ Hikvision.com

Hikvision Singapore
T +65 6589 4716
sg@ Hikvision.com

Hikvision Spain
T +34 91 737 18 50
info.es@ Hikvision.com

Hikvision Tashkent
T +99 87 7208 0408
uzb@ Hikvision.ru

Hikvision Hong Kong
T +852 2151 1761
info.hk@ Hikvision.com

Hikvision Russia
T +7 495 868 87 88
sales.ru@ Hikvision.com

Hikvision Korea
T +82 10 31 731 6817
sales.korea@ Hikvision.com

Hikvision Poland
T +48 22 460 00 60
info.pl@ Hikvision.com

Hikvision Indonesia
T +62 21 2933250
Sales.Indonesia@ Hikvision.com

Hikvision Colombia
sales.colombia@ Hikvision.com