

DHI-ASR2201A-D

Access Reader



Series Overview

General

RS-485

As a key part of the access control system, the DHI-ASR2201A-D access control card reader supports card and password unlock, and sends the information to the access controller for verification. With a thin and elegant design, it is applicable to industrial zones, office buildings, schools, factories, stadiums, CBD, residential area, government properties, etc.

| properties, etc. | | | |
|-------------------------|---|--|--|
| Technical Specification | | | |
| Basic | | | |
| Product Type | Slim Card Reader | | |
| Buzzer | Yes | | |
| Casing | Tempered glass/PC | | |
| Function | | | |
| Unlock Mode | Card swiping/password Multiple unlocking modes | | |
| Card Type | ID card | | |
| Performance | | | |
| Response Time | 0.1 s | | |
| Card Reading Distance | 0 cm–5 cm (0"–1.97") | | |
| Port | | | |
| RS-485 | 1 channel | | |
| Wiegand | 1 output channel | | |
| Alarm | | | |
| Tamper Alarm | Yes | | |

1 channel

- PC material, tempered glass panel and IP66, suitable for indoor and outdoor use
- Support contacless recognition of ID card
- Support card/password unlock
- Support RS-485 and Wiegand communication protocol
- Support buzzer and indicator prompt
- Support anti-tampering alarm
- The built-in watchdog can detect and control the abnormal operation status of the equipment and perform recovery processing to ensure the long-term operation of the equipment
- All connection ports have overcurrent and overvoltage protection









| Power Supply | 12V 0.5A DC | |
|-----------------------|---|--|
| Protection | IP66 (silicon sealant is needed, see the manual) | |
| Power Consumption | Standby ≤ 0.9W, working ≤ 1.7W | |
| Product Dimensions | 135 mm × 40 mm × 15 mm (5.31" × 1.57" × 0.59") (L × W× H) | |
| Packaging Dimensions | 195 mm × 75 mm × 52 mm (7.68" × 2.95 × 2.05") (L × W× H, 1 in inner carton) 415 mm × 400 mm × 230 mm (16.34" × 15.75" × 9.06") (L × W × H, carton) | |
| Operating Temperature | −30°C to +70°C (−22°F to +158°F) | |
| Operating Humidity | 5%RH–95% (non-condensing) | |
| Operating Environment | Indoor; outdoor | |
| Gross Weight | 0.16 kg (0.35 lb) | |
| Installation | Surface mount | |
| Certifications | CE; FCC | |

ASR2 Series | DHI-ASR2201A-D

| Ordering Information | | | |
|----------------------|----------------|--|--|
| Туре | Model | Description | |
| Access Reader | DHI-ASR2201A-D | DHI-ASR2201A-D Outdoor Waterproof Password ID Card Reader Slim Model | |

Dimensions (mm[inch])



