

DS-2CE10DFT-F 2 MP Full Time Color Bullet Camera

ColorVu



Key Feature

- 2 MP high performance CMOS
- 1920 × 1080 resolution
- Full time color
- 3.6 mm, 6 mm fixed lens
- Up to 20 m white light distance
- OSD menu, 3D DNR, true WDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67
- Up the coax (HIKVISION-C)




Specification

Camera	
Image Sensor	2 MP CMOS image sensor
Resolution	1920 (H) × 1080 (V)
Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Min. illumination	Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Slow Shutter	Max. 16x
Lens	3.6 mm, 6 mm fixed lens
Field of View	3.6 mm, horizontal FOV: 83.0°, vertical FOV: 44.4°, diagonal FOV: 98.0° 6 mm, horizontal FOV: 51.0°, vertical FOV: 28.5°, diagonal FOV: 58.7°
Lens Mount	M16
Day & Night	Color
Angle Adjustment	Pan: 0° to 360°; Tilt: 0° to 180°; Rotate: 0° to 360°
Synchronization	Internal synchronization
WDR (Wide Dynamic Range)	130 dB
Menu	
Image Mode	STD/HIGH SAT
AGC	Yes
White Balance	Auto/Manual
HLC	Yes
BLC (Backlight Compensation)	Yes
Privacy Mask	4 programmable privacy masks
Motion Detection	4 programmable areas
WDR	Yes
Functions	Brightness, Sharpness, 3D DNR, Mirror, Smart light
Interface	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ±25% <i>*You are recommended to use one power adapter to supply the power for one camera.</i>
Power Consumption	Max. 3 W
Protection Level	IP67
Material	Metal
White Light	Up to 20 m
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Dimensions	181.4 mm × 70 mm × 68 mm (7.14" × 2.75" × 2.68")
Weight	Approx. 390 g (0.86 lb.)


Order Model

DS-2CE10DFT-F

Dimension



Accessory



DS-1280ZJ-XS

Junction Box

Distributed by

Headquarters
No.555 Dianmo Road, Binjiang District,
Hangzhou 310061, China
T: +86-571-8807-5888
overseasbusiness@hikvision.com

Hikvision USA
T: +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T: +39-0438-6802
info.it@hikvision.com

Hikvision Singapore
T: +65-6684-4718
sg@hikvision.com

Hikvision Europe
T: +31-23-5542770
sales.eu@hikvision.com

Hikvision France
T: +33011-85-330-444
info.fr@hikvision.com

Hikvision Oceania
T: +61-2-8599-4233
sales.au@hikvision.com

Hikvision Middle East
T: +871-4-8816086
sales.me@hikvision.com

Hikvision Spain
T: +34-91-737-16-55
info.es@hikvision.com

Hikvision Hong Kong
T: +852-2151-1761

Hikvision Russia
T: +7-495-669-67-89
sales.ru@hikvision.com

Hikvision Poland
T: +48-22-460-01-60
poland@hikvision.com

Hikvision Canada
T: +1-909-895-0400
sales.ca@hikvision.com

Hikvision India
T: +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T: +44-1628-9021-4
support.uk@hikvision.com