

## DS-D4212FI-MWF/III Full-Color LED Display

DS-D4212FI-MWF/III is the new generation small pixel pitch indoor full-color LED display. LED video wall features in seamlessness, high brightness/contrast, wide viewing angle, and accurate color restoration, achieving good visual effect. It is widely used in places such as monitoring center, command center, conference room, report hall, and exhibition hall.




- Seamlessly splice images in rows and columns.
- Easily form standard 1920 × 1080 and 3840 × 2160 screens, achieving high definition dot-by-dot display.
- Automatically adapt signal sources to screens without the help of a video processing equipment.
- Easily optimize images with low resolution by improving definition, contrast and saturation with Pix Master technology.
- Dynamically enhance image parameters such as contrast, sharpness, saturation, color temperature and gamut to get the image more vivid.
- A signal input of 4K resolution at 30 Hz, and an output of up to 4K resolution for a single device.
- Use the buttons on the panel of sending card to adjust brightness and switch signal.
- Use the Hikvision remote control (optional) to navigate through menu after access to the multi-functional card.
- Automatically remove moisture to protect lamp boards from water damage when the device is kept in a humid environment or left unused for a long time.
- Back up signals and power supplies (optional) to maintain a reliable system.
- Real-time cabinet temperature and voltage checking to guarantee product safety.
- Use the sending card to input HDMI, DVI, and DP signals.
- Network interface output.
- Remote configuration via the debugging network interface.
- Easy to disassemble lamp board, power supply, and receiving card on the front side with modular unit structure.
- Precise fool-proof design of lamp boards with magnetic adsorption to prevent wrong installation.
- Three-axis XYZ structure designed to perfectly adjust the flatness of the entire screen.
- Rapidly eliminate bright and dim lines with no need of professional equipment or operations.




## ▪ Specification

Model		DS-D4212FI-MWF/III
Cabinet	Pixel Configuration	SMD Triad LED
	Pixel Pitch Category	P1.2
	Pixel Pitch	1.25 mm
	Lamp Dimensions	1.0 × 1.0 mm
	Modules Component	2 × 4
	Dimensions (W × H × D)	600 mm × 337.5 mm × 50.9 mm (23.62" × 13.29" × 2.00")
	Resolution	480 × 270
	Area	0.2 m <sup>2</sup>
	Weight	5.4 Kg (11.9 lb)
	Pixel Density	640000 dots/m <sup>2</sup>
	Lamp Board Housing	With housing
	Cabinet Material	Magnalium
	Maintenance Method	Front maintenance for all components
	Cabinet Flatness	0.1 mm
	Protection Level	Front protection level IP60
Key Material	Lamp Encapsulation	Nationstar 1010
	Driver IC	ICN2065
	Control System	DS-D42C04-H、DS-D42C08-H、DS-D42C16-H
Display	White Balance Brightness	800 cd/m <sup>2</sup>
	Color Temperature	3000 K to 10000 K adjustable
	Viewing Angle	Horizontal 160°, vertical 160°
	Contrast Ratio	≥ 5000:1
	Color Uniformity	≤ ± 0.003Cx, Cy
	Brightness Uniformity	≥ 97%
Processing Performance	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	Up to 3840 Hz
	Grey Level	Up to 16 bit
	Display Color	281 trillion
Power	Power Supply	110~220 VAC ± 15%
	Max. Consumption	≤ 600 W/m <sup>2</sup>
	Average Consumption	< 200 W/m <sup>2</sup>
Working Environment	Working Temperature	-10~40 °C
	Working Humidity	10%~60%RH
	Storage Humidity	10%~85%RH
	Storage Temperature	-20~60 °C
General	Gross Weight	9.6 Kg (21.2 lb)
	Package Dimension (W × H × D)	796 mm × 484 mm × 192 mm (31.33" × 19.05" × 7.56")
	Lifespan	Lamp 100,000 hours

## ▪ Typical Application



## ▪ Dimension



- Accessory
- Optional

## DS-D42C04-H LED Control Card



## ▪ Available Model

DS-D4212FI-MWF600\*337.5MM

DS-D4212FI-MWF/A

Distributed by



# HIKVISION

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou, 310051, China  
T +86-571-8607-5008  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-865-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8690-4233  
sales.au@hikvision.com

**Hikvision India**  
T +91-22-28469000  
sales@pmahikvision.com

**Hikvision Canada**  
T +1-800-380-6890  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-3646  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-3642770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0439-6802  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3315-0850  
latam.support@hikvision.com

**Hikvision Turkey**  
T +90 12160217070-7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +41320-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
T +27 11 01 0361172  
sales.africa@hikvision.com

**Hikvision France**  
T +33 01-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-8730667  
nikitapantikov@hikvision.ru

**Hikvision Vietnam**  
T +84 979270898  
sa.gu.vi@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
sales.me@hikvision.com

**Hikvision Singapore**  
T +65-6884-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9432  
info@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1700  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-660-67-00  
sales.ru@hikvision.com

**Hikvision Korea**  
T +82-10151-731-8617  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-463-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2932759  
Sales.indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com