




PL10D

recognition technology. It is the same with PL10, german standard mortise with one latch and one deadbolt. You can turn handle upward to

Features

- With the new generation fingerprint recognition algorithm
- Rugged, sleek and compact design
- German standard mortise with one latch and one deadbolt External terminals to draw back-up power - turn handle upward to lock the deadbolt for more security
- Independent clutch motor design under patent protection
- Idle handle design to prevent from forcible entry
- Registration data are stored even if there is power loss
- Handle, lock body and strike is reversible design for all door open direction
- Capacitive sensing technology Touch to open.

- Emergency key override (concealed)
- · LED indicator and inbuilt buzzer
- from a 9V battery
- Low battery warning
- Normal Open mode
- Easy to program and easy to use
- Easy to install-no wiring required
- 3 user groups Admin, Normal User and Temporary User
- Backset is 62mm



Specifications

Material	Rugged ABS
User Capacity	Admin -10
	Normal User - 60
	Temporary User - 20
Operating Temperature	-20°C - 55°C
Power Supply	4×AA Alkaline Battery
Backup Unlocking Way	Mechanical Key & 9V Battery
Door Thickness	30-38 mm (optional)
	39-46 mm (standard)
	47-54 mm (standard)
	55-60 mm (optional)
Dimensions	Front - 69(W)×155(L)×35(D) mm
	Back - 69(W)×155(L)×25(D) mm



