

NKB1000-E

Network Keyboard



Features :

Keyboard to Control

- Dahua High Speed Dome
- Dahua Standalone DVR
- Network Video Server

Connection

- RS485, RS422 (reserved), USB, RS232 & Network

Functions

- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern

Auxiliary Functions

- On-Screen Menu & User Operation Procedure Tips
- Connect to SmartPSS or DSS platform via USB

3-axis

USB
Control

RJ-45
port



Technical Specification

Model

Model NKB1000-E

General

Keyboard Key panel Electromechanical

Joystick 3-axis, vector-solving, with twisting, return to-center head

Keyboard Connector RJ-45, RS232, RS485, RS422 (reserved), USB

Keyboard Communication Direct Mode, Network Mode

Direct Mode Interface:
1 RS232/2 RS485
DVR Protocol: DH-2
Dome Protocol: DH-SD1/PELCO-D/PELCO-P, etc

Network Mode Interface: RJ45
DVR/Network Dome:
IP Address/Port/Protocol

Display LCD, 75.2mm×33.85mm

Maximum Number of Users 64 (including "admin")

Max RS485 Addresses (Each User) 256

Max Number of PTZ (IPC) That Can be Added over Network (Each User) 2048

Environmental

Power Supply	Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/2A
Power Consumption	5W
Working Temperature	-10℃~+55℃
Working Humidity	10% ~ 90%
Atmosphere Pressure	86kpa~106kpa
Dimension	330mm×139mm×53mm (W×D×H)(height: 103mm including joystick)
Weight	1.3kg (Including package)

Dimensions(mm)

