# DS-PEA4H-10
# Panic Alarm Master Station

The DS-PEA4H-10 master station supports functions such as live view, intercom, device call, etc. It is equipped with 10.1- inch high definition touch screen that displays flat-design interface. The master station applies to security areas such as school, square, hospital, shopping mall, station market, park, etc.

## ▪ Key Features

- 10.1-inch touch screen
- Real-time alarm information display
- Supports microphone rod and VGA
- Supports auto noise suppression and echo cancellation
- Easy installation with Power over Ethernet (PoE) technology

## ▪ Specification

| | |
|---|---|
| **Software features** | |
| Intercom | Built-in Microphone, Handset、 loudspeaker |
| Protocol | TCP/IP, HIK-SIP, and RTSP |
| **Hardware features** | |
| Alarm input | 4 |
| Alarm output | 4 |
| Relay output | 4, relay output |
| Netowrk interface | 1RJ45,10 M/100 M/1000 M self adaptive |
| Serial port | 2, RS-485 half-duplex interface |
| Video interface | VGA ， HDMI |
| Audio interface | Built-in microphone, handset, and mic support |
| USB | 1, USB 3.0<br>1, USB 2.0 |
| PSTN | RJ11, 1 for handset |
| SD Card | 1, Micro SDXC (≤ 128 GB) |
| **Video** | |
| Frame rate | PAL: 25 FPS, NTSC: 30 FPS |
| **Electrical characteristics** | |
| Power supply | 12 VDC, PoE (IEEE 802.3 at/af) |
| Power Consumption | ≤15 W |
| **Display** | |
| Display screen | 10.1 inch colorful TFT LCD, 1280 × 800 |
| User interface | Flat design |
| **General** | |
| Operation temperature | -10 ℃ to 55 ℃ |
| Operation humidity | 10% to 90% |
| Dimension(WxHxD) | with handset: 361mm (14.2 inch) × 65mm (2.6 inch) ×<br>197mm (7.8 inch) without handset: 291mm (11.5 inch) ×<br>41mm (1.6 inch) × 197mm (7.8 inch) |
| Weight | ≤2.5 kg (88.2 oz) |
| **Audio** | |
| Audio input | Built-in microphone, handset, and mic support |
| Audio output | Built-in loudspeaker, and handset |
| Audio compression code rate | 16Kbps,64Kbps |
| **Device management** | |
| Camera | CMOS, 2 MP |

## ▪ Available Model

DS-PEA4H-10

Distributed by


**Headquarters**
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

**Hikvision USA**
T +1-909-895-0400
sales.usa@hikvision.com

**Hikvision Europe**
T +31-23-5542770
sales.eu@hikvision.com

**Hikvision UK & Ireland**
T +01628-902140
sales.uk@hikvision.com

**Hikvision UAE**
T +971-4-4432090
salesme@hikvision.com

**Hikvision Russia**
T +7-495-669-67-99
sales.ru@hikvision.com

**Hikvision Australia**
T +61-2-8599-4233
sales.au@hikvision.com

**Hikvision Italy**
T +39-0438-6902
info.it@hikvision.com

**Hikvision South Africa**
Tel: +27(0)10 35 1172
sale.africa@hikvision.com

**Hikvision Singapore**
T +65 6684 4718
sg@hikvision.com

**Hikvision Korea**
T +82 (0)31 731 8817
sales.korea@hikvision.com

**Hikvision India**
T +91 22 28469900
sales@pramahikvision.com

**Hikvision Brazil**
T +55 11 3318-0050
Latam.support@hikvision.com

**Hikvision France**
T +33(0)1-85-330-450
info.fr@hikvision.com

**Hikvision Spain**
T +34-91-737-16-55
info.es@hikvision.com

**Hikvision Poland**
T +48 22 460 01 50
info.pl@hikvision.com

**Hikvision Canada**
T +1 866 200 6690
sales.canada@hikvision.com

**Hikvision Turkey**
T +90 (216) 521 7070- 7074
sales.tr@hikvision.com

**Hikvision Kazakhstan**
T +7-727-9730667
nikita.panfilov@hikvision.ru

**Hikvision Tashkent**
T +998-97-1239-9438
uzb@hikvision.ru

**Hikvision Indonesia**
T +62 21 2933 7599
Sales.indonesia@hikvision.com

**Hikvision Thailand**
T +662-275-3949
sales.thailand@hikvision.com

**Hikvision Malaysia**
T +603- 7652 2412
sales.my@hikvision.com

**Hikvision Vietnam**
T +84 9762 03688
sales.vt@hikvision.com

**Hikvision Hong Kong**
T +852 2151 1761
info.hk@hikvision.com

**Hikvision Colombia**
sales.colombia@hikvision.com


© Hikvision Digital Technology Co., Ltd. 2020 | Data subject to change without notice |